

Sirca
THE WOOD COATINGS



KATILAC COATINGS INC.



CLEAR POLYURETHANE SYSTEMS

ITALIAN POLYURETHANE TECHNOLOGY

CLEAR POLYURETHANE SYSTEMS

SEALERS

6FPI35S06 Insulating Agent

An insulating agent for use under polyurethane and polyester products. It is recommended for exotic woods such as rosewood, teak and iroko that are rich in tannin.

- 18% weight solids, 15% volume solids
- 17" viscosity Zahn 2 @ 20°C
- 2-6 hours to overcoat (without sanding)
- 100% catalyzation with 6TC20; 20-50% reduction with SOL-0041
- 3 hrs pot-life
- 1-2 coats applied at 3-5 wet mils

6FPU52 Very Clear PU Sealer

A general purpose clear polyurethane sealer that has excellent clarity and high build.

- 48% weight solids, 42% volume solids
- 80" viscosity Zahn 4 @ 20°C
- 120 min to sand
- 50% catalyzation by weight with 6CTH3
- >2 hrs potlife if reduced with SOL-9054 at 20%

TOPCOATS

60PU77S15G Clear PU Topcoat

A general purpose polyurethane topcoat that is characterized by a good build and levelling.

- 47% weight solids, 44% volume solids
- 20" viscosity Zahn 4 @ 20°C
- 12 hours to stack
- 10,30,40,50 & 80 degree sheens
- 50% catalyzation by weight with 6CTH3
- > 2hrs pot life if reduced with SOL-9054 at 20%



ITALIAN POLYURETHANE TECHNOLOGY



Sirca is a global leader in the development and manufacturing of the highest quality industrial wood coatings. The Sirca line is a broad assortment of industry leading technologies including clear & pigmented polyurethanes, acrylic polyurethanes, waterborne & UV coatings, interior & exterior systems and stains.

Katilac Coatings Inc. (KCI), a Canadian manufacturer of conventional acid cured wood coatings including pre- and post-catalyzed lacquers, conversion varnishes, waterborne finishes and colour systems. KCI is Sirca's partner to bring their Italian finishes to the Canadian market.

www.katilaccoatings.com



KATILAC COATINGS INC.