



SECTION 1 – PRODUCT IDENTIFICATION AND COMPANY IDENTIFICATION

Manufacturer/Supplier: KATILAC COATINGS INC.
391 HANLAN ROAD, UNIT #1, WOODBRIDGE, ONTARIO L4L 3T1
Phone:..... 905-856-6464
840 APPLEBY LINE, BURLINGTON, ONTARIO L7L 2Y7
Phone:..... 905-637-2931
www.katilaccoatings.com
Emergency Phone:..... CANUTEC (24H)...1-888-CANUTEC (226-8832 North American use)
.....1-613-996-6666 (International use)
Poison Control:..... 800-268-9017
Revision Date:..... January 12, 2021
Print Date:..... November 10, 2020
Version Number:..... 3
Product: AE SERIES AQUA-ELITE WATERBORNE ACRYLIC TOPCOAT
Product Use: INDUSTRIAL COATING
FOR INDUSTRIAL USE ONLY

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

Target Organs:

None

GHS Classification:

Not Classified under GHS criteria.

GHS Label Elements, including precautionary statements:

Pictogram:

Not required

Signal Word:..... Not required

Hazard Statement(s):

Not required

Precautionary Statement(s):

Not required

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	%
Dipropylene Glycol Monomethyl Ether	34590-94-8	1.00-5.00
2-propanol, 1-propoxy-	1569-01-3	3.00-7.00

Refer to Section 8 for Occupational Exposure Guidelines.

SECTION 4 – FIRST-AID MEASURES

Inhalation:

If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical advice.

Ingestion:

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Have victim drink 60-240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim rinse mouth with water again. Obtain medical advice.

Eyes:

No effects expected. If irritation occurs, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

Skin:

No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

Note to Physician:

Treatment should be based on sound judgement of physician and individual reactions of patient.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media:

Foam, water spray, dry chemical, carbon dioxide.

Special Fire Fighting Procedures:

Not available.

Unusual Fire and Explosion Hazards:

Sensitivity to static discharge is not expected.

Hazardous Combustion Products:

Carbon monoxide and/or carbon dioxide. Silicone compounds, formaldehyde, phosphorous oxides, sulphur oxides.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Beware of vapours accumulating.

Safety Data Sheet - AE SERIES AQUA-ELITE WATERBORNE ACRYLIC TOPCOAT

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Dike and contain spills. Do not let product enter drains.

Methods and Materials for Containment and Clean Up:

Contain and/or dike spills. Absorb with inert material, place in a suitable container. Report and dispose of according to local regulations.

SECTION 7 – HANDLING AND STORAGE

Storage:

Keep container tightly closed in a dry and well-ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage and evaporation. Do not freeze.

Handling:

Use in a well ventilated area. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value:..... Not available.

Engineering Controls:

Use local, mechanical, explosion proof exhaust and/or ventilation system to avoid exposure and vapour accumulation.

Personal Protective Equipment:

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate, use an approved respirator for the concentration and type of hazardous materials in the workplace. Use respirators and components tested and approved under the appropriate government standards. Use respirators as backup to engineering controls if necessary.

Hand Protection:

Handle with gloves to minimize skin contact. Inspect gloves prior to use. Use proper glove removal technique (without touching the glove's outer surface) to avoid skin contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly.

Eye Protection:

Safety glasses and/or face shield. Use equipment for eye protection tested and approved under the appropriate government standards.

Protective Clothing:

Impervious clothing. The type of protective equipment should be selected according to the concentration and amount of hazardous materials at each specific workplace.

Additional Measures:

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and at the end of the workday.

SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

Physical State: Liquid
Appearance/Odour: Clear with mild odour
Odour Threshold: Not available
Viscosity: 30-40 seconds @ 25°C #4 Ford Cup
Vapour Density (AIR=1): Not available
Boiling Point: >100°C
Melting/Freezing Point: Not available
Vapour Pressure: Not available
Evaporation Rate: Not available
Specific Gravity: 1.0050 +/- 0.01 gms/CC
Solubility in Water: No data
% Non-Volatile: 31% +/- 2 w/w
 28% +/- 2 w/v
Coeff. Water/Oil Dist.: Not available
VOC 98 g/L

Flashpoint: Not available
Autoignition Temp: Not available
Upper Flammable Limit: Not available
Lower Flammable Limit: Not available

SECTION 10 – STABILITY AND REACTIVITY

Stability:

Stable under normal conditions. Hazardous polymerization not expected.

Hazardous Decomposition Products:

Carbon monoxide and/or carbon dioxide. Aldehydes, ketones, silicone compounds, formaldehyde, organic acids.

Materials to Avoid:

Avoid contact with water reactive materials, heat or contact with peroxides or other catalysts. Strong oxidizing agents. Strong acids, strong bases. Aluminum and some galvanized metals.

Hazardous Reactions:

No data.

Conditions to Avoid:

Freezing and/or cold temperatures.

SECTION 11 – TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT	LD50	LC50	HRS
Dipropylene Glycol Monomethyl Ether	5152 mg/kg	not available	-
2-propanol, 1-propoxy-	2490 mg/kg	not available	-

Skin corrosion/irritation:

Not classified as a skin irritant.

Serious eye damage/irritation:

Not classified as an eye irritant.

Safety Data Sheet - AE SERIES AQUA-ELITE WATERBORNE ACRYLIC TOPCOAT

Respiratory or skin sensitization:

Not classified as a sensitization hazard.

Germ cell mutagenicity:

Not expected to be mutagenic in humans.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity:

Not classified as a reproductive toxicant.

Teratogenicity:

Not available.

Specific target organ toxicity (single exposure):

Not classified as a single exposure toxicant.

Specific target organ toxicity (repeated exposure):

Not classified as a repeat exposure hazard.

Aspiration hazard:

Not classified as an aspiration hazard.

Potential Health Effects:**Inhalation:**

No significant signs or symptoms are expected. Excessive inhalation may irritate respiratory tract.

Ingestion:

Not a likely route of exposure.

Skin:

Prolonged or repeated contact may cause irritation.

Eyes:

Not expected to cause eye irritation under safe, normal working conditions. Can cause slight, temporary eye irritation upon contact.

Signs and Symptoms of Exposure:

No symptoms expected under normal working conditions.

Synergistic effects:

No data.

Additional information:

Not available.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental Fate and Distribution:

Prevent from entering drains, sewers, streams or other bodies of water. If runoff occurs, notify authorities as required.

Aquatic toxicity:

LC50 >1000 mg/L (Poecilia Reticulata), static, 96H, OECD Test Guideline 203, est. (Dipropylene Glycol Monomethyl Ether)

LC50 >100 mg/L (Oncorhynchus Mykiss), static, 96H, OECD Test Guideline 203, est. (2-propanol, 1-propoxy-)

Safety Data Sheet - AE SERIES AQUA-ELITE WATERBORNE ACRYLIC TOPCOAT

Persistence and degradability:

No data.

Bioaccumulative potential:

No data.

Mobility in soil:

No data.

Other adverse effects:

No data.

SECTION 13 –DISPOSAL CONSIDERATIONS

Waste disposal:

Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of in accordance with all applicable regulations.

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may retain product residue, follow any label warnings even after container is emptied.

SECTION 14 – TRANSPORTATION INFORMATION

TDG Classification (Ground Only):NON REGULATED

Proper Shipping Name (Ground Only):NON REGULATED

A scientific determination was concluded based on formulation ingredients on September 19, 2018 to define the Transportation of Dangerous Goods Classifications.

SECTION 15 - REGULATIONS

This material is included on the DLS (Canadian Domestic Substance List) under the CEPA (Canadian Environmental Protection Act).

This material has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This material meets TSCA (Toxic Substances Control Act) inventory requirements.

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

SECTION 16 – OTHER INFORMATION

LEGEND TO ABBREVIATIONS:

CAS: CHEMICAL ABSTRACT SERVICES

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

LC: LETHAL CONCENTRATION

LD: LETHAL DOSE

TDG: TRANSPORTATION OF DANGEROUS GOODS

TLV: THRESHOLD LIMIT VALUE

VOC: VOLATILE ORGANIC COMPOUND

The information contained in this form is based on data from sources considered to be reliable but Katilac Coatings Inc. does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Katilac Coatings Inc. expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.