

SECTION 1 – PRODUCT IDENTIFICATION AND COMPANY IDENTIFICATION

Manufacturer/Supplier: KATILAC COATINGS INC.

391 HANLAN ROAD, UNIT #1, WOODBRIDGE, ONTARIO L4L 3T1

Phone:......905-856-6464

840 APPLEBY LINE, BURLINGTON, ONTARIO L7L 2Y7

Phone:......905-637-2931

www.katilaccoatings.com

Emergency Phone:......CANUTEC (24H)...1-888-CANUTEC (226-8832 North American use)

.....1-613-996-6666 (International use)

Poison Control:..... 800-268-9017

Revision Date:..... January 19, 2021 Print Date:..... January 19, 2021

Version Number:.....3

Product: B7385 VISTA WATERBORNE DRY GLAZE BASE

Product Use: INDUSTRIAL COATING

FOR INDUSTRIAL USE ONLY

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

Target Organs:

Lungs.

GHS Classification:

Skin Sensitizer (Cat. 1) Carcinogenicity (Cat. 1A)

Specific Target Organ Toxicity - Repeated Exposure (Cat. 1) - Lungs

GHS Label Elements, including precautionary statements:

Pictogram:





Signal Word:..... Danger

Hazard Statement(s):

H317: May cause an allergic skin reaction

H350: May cause cancer

H372: Causes damage to organs through prolonged or repeated exposure

Precautionary Statement(s):

P202: Do not handle until all safety precautions have been read and understood

P280: Wear protective gloves/protective clothing/eye protection/face protection

P362+364: Take off contaminated clothing and wash it before reuse

P272: Contaminated work clothing should not be allowed out of the workplace

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P264: Wash skin thoroughly after handling

P270: Do not eat, drink or smoke when using this product

P308+313: IF exposed or concerned: Get medical advice/attention

P302+352: IF ON SKIN: Wash with soap and water

P333+313: If skin irritation or a rash occurs: Get medical advice/attention

P314: Get Medical advice/attention if you feel unwell

P405: Store locked up

P501: Dispose of contents/container to comply with local, provincial, state, and federal regulations

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

 HAZARDOUS INGREDIENT
 CAS NUMBER
 %

 Calcium Carbonate
 1317-65-3
 10.00-30.00

 Crystalline Silica Quartz
 14808-60-7
 0.10-1.00

 Tetramethyl-5-decyne-4,7-diol,2,4,7,9 126-86-3
 0.10-1.00

Refer to Section 8 for Occupational Exposure Guidelines.

SECTION 4 - FIRST-AID MEASURES

Inhalation:

If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical advice.

Ingestion:

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Have victim drink 60-240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Obtain medical advice.

Eyes:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding eyelid(s) open. Obtain medical advice.

Skin:

Remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decominate clothing, shoes and leather goods before reuse or discard.

Note to Physician:

Treatment based on sound judgement of physician and individual reactions of patient.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media:

Foam, water spray, dry chemical, carbon dioxide.

Special Fire Fighting Procedures:

Not available.

Unusual Fire and Explosion Hazards:

Sensitivity to static discharge is not expected.

Hazardous Combustion Products:

Carbon monoxide and/or carbon dioxide, aldehydes, hydrocarbons, ammonia, amines.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Beware of vapours accumulating.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Dike and contain spills. Do not let product enter drains.

Methods and Materials for Containment and Clean Up:

Contain and/or dike spills. Absorb with inert material, place in a suitable container. Report and dispose of according to local regulations.

SECTION 7 – HANDLING AND STORAGE

Storage:

Keep container tightly closed in a dry and well-ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage and evaporation. Do not freeze.

Handling:

Use in a well ventilated area. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value:..... Not available

Engineering Controls:

Use local, mechanical, explosion proof exhaust and/or ventilation system to avoid exposure and vapour accumulation.

Personal Protective Equipment:

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate, use an approved respirator for the concentration and type of hazardous materials in the workplace. Use respirators and components tested and approved under the appropriate government standards. Use respirators as backup to engineering controls if necessary.

Hand Protection:

Handle with gloves to minimize skin contact. Inspect gloves prior to use. Use proper glove removal technique (without touching the glove's outer surface) to avoid skin contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly.

Eye Protection:

Safety glasses and/or face shield. Use equipment for eye protection tested and approved under the appropriate government standards.

Protective Clothing:

Impervious clothing. The type of protective equipment should be selected according to the concentration and amount of hazardous materials at each specific workplace.

Additional Measures:

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and at the end of the workday.

SECTION 9 - PHYSICAL / CHEMICAL PROPERITES

Physical State: Liquid

Appearance/Odour: Hazy, white liquid with mild odour

Odour Threshold: Not available

Viscosity:......25-35 seconds Ford #4 @ 25°C

Specific Gravity: 1.1496 +/- 0.01 gms/cc @ 25°C

SECTION 10 – STABILITY AND REACTIVITY

Stability:

Stable under normal conditions. Hazardous polymerization not expected.

Hazardous Decomposition Products:

Carbon monoxide and/or carbon dioxide. Calcium oxide, aldehydes.

Materials to Avoid:

Avoid contact with water reactive materials, heat or contact with peroxides or other catalysts. Fluorine, acids, aluminum, ammonia salts, oxidizing agents, reactive metals, sodium hypochlorite, calcium hypochlorite, zinc, dehydrating agents, peroxides.

Hazardous Reactions:

No data.

Conditions to Avoid:

Freezing and/or cold temperatures.

SECTION 11 - TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT	LD50	LC50	HRS
Calcium Carbonate	5000 mg/kg	not available	-
Crystalline Silica Quartz	not available	not available	-
Tetramethyl-5-decyne-4,7-diol,2,4,7,9-	not available	not available	-
		20.53% of total product	
		has unknown toxicity	

Skin corrosion/irritation:

Not classified as a skin irritant.

Serious eye damage/irritation:

Not classified as an eye irritant.

Respiratory or skin sensitization:

Not classified as a sensitization hazard.

Germ cell mutagenicity:

Not expected to be mutagenic in humans.

Carcinogenicity:

IARC has classified Crystalline Silica Quartz as carcinogenic to humans, Group 1.

Reproductive toxicity:

Not classified as a reproductive toxicant.

Teratogenicity:

Not available.

Specific target organ toxicity (single exposure):

Not classified as a single exposure toxicant.

Specific target organ toxicity (repeated exposure):

May cause lung effects.

Aspiration hazard:

Not classified as an aspiration hazard.

Potential Health Effects:

Inhalation:

No significant signs or symptoms are expected. Excessive inhalation may irritate respiratory tract. Studies have linked excessive inhalation of calcium carbonate and crystalline silica, quartz in dust form with chronic respiratory disease. Coatings risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

Ingestion:

Not a likely route of exposure. Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

Skin:

Little or no skin irritation expected under safe handling conditions.

Eves:

Not expected to cause eye irritation under safe, normal working conditions.

Signs and Symptoms of Exposure:

Repeated overexposure to high respirable concentrations can cause lung effects.

Synergistic effects:

None known.

Additional information:

Studies have linked excessive inhalation of calcium carbonate and crystalline silica, quartz in dust form with chronic respiratory disease. Coatings risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate and Distribution:

Prevent from entering drains, sewers, streams or other bodies of water. If runoff occurs, notify authorities as required.

Aquatoxicity:

LC50 (Oncorhynchus Mykiss) >10000 mg/L 96H est.

Persistence and degradability:

No data.

Bioaccumulative potential:

No data.

Mobility in soil:

No data.

Other adverse effects:

No data.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal:

Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of in accordance with all applicable regulations.

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may retain product residue, follow any label warnings even after container is emptied.

SECTION 14 – TRANSPORTATION INFORMATION

TDG Classification (Ground Only):NON REGULATED Proper Shipping Name (Ground Only):NON REGULATED

A scientific determination was concluded based on formulation ingredients on September 11, 2019 to define the Transportation of Dangerous Goods Classifications.

SECTION 15 - REGULATIONS

This material is included on the DLS (Canadian Domestic Substance List) under the CEPA (Canadian Environmental Protection Act).

This material has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This material meets TSCA (Toxic Substances Control Act) inventory requirements.

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

SECTION 16 – OTHER INFORMATION

LEGEND TO ABBREVIATIONS:

CAS:	CHEMICAL ABSTRACT SERVICES
IARC:	INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
LC:	LETHAL CONCENTRATION
LD:	LETHAL DOSE
TDG:	TRANSPORTATION OF DANGEROUS GOODS
TLV:	THRESHOLD LIMIT VALUE
VOC:	VOLATILE ORGANIC COMPOUND

The information contained in this form is based on data from sources considered to be reliable but Katilac Coatings Inc. does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Katilac Coatings Inc. expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.