



SECTION 1 – PRODUCT IDENTIFICATION AND COMPANY IDENTIFICATION

Manufacturer/Supplier: KATILAC COATINGS INC.
391 HANLAN ROAD, UNIT #1, WOODBRIDGE, ONTARIO L4L 3T1
Phone:..... 905-856-6464
840 APPLEBY LINE, BURLINGTON, ONTARIO L7L 2Y7
Phone:..... 905-637-2931
www.katilaccoatings.com

Emergency Phone:.....CANUTEC (24H)...1-888-CANUTEC (226-8832 North American use)
.....1-613-996-6666 (International use)

Poison Control:..... 1-800-268-9017

Revision Date:..... January 20, 2021
Print Date:..... January 20, 2021
Version Number:..... 4

Product: E15 OMNIPRIME NEUTRAL PRE-CATALYZED PRIMER
Product Use: NEUTRAL PRE-CATALYZED PRIMER
FOR INDUSTRIAL USE ONLY

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

Target Organs:

Kidney, liver, reproductive system, central nervous system, eyes, skin.

GHS Classification:

Flammable Liquids (Cat. 2)
Skin Irritation (Cat. 2)
Serious Eye Damage (Cat. 1)
Carcinogenicity (Cat. 1)
Reproductive Toxicity (Cat. 1B)
Specific Target Organ Toxicity- Single Exposure (Cat. 3) - Central Nervous System
Specific Target Organ Toxicity- Single Exposure (Cat. 2) - Ingestion may damage optic nerve
Specific Target Organ Toxicity - Repeated Exposure (Cat. 1)

Safety Data Sheet - E15 OMNIPRIME NEUTRAL PRE-CATALYZED PRIMER

GHS Label Elements, including precautionary statements:

Pictogram:



Signal Word:..... **Danger**

Hazard Statement(s):

H225: Highly flammable liquid and vapour
H315: Causes skin irritation
H318: Causes serious eye damage
H350: May cause cancer
H360: May damage fertility or the unborn child
H336: May cause drowsiness or dizziness
H371: May cause damage to organs - ingestion may damage optic nerve
H372: Causes damage to organs through prolonged or repeated exposure

Precautionary Statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233: Keep container tightly closed
P240: Ground/bond container and receiving equipment
P241: Use explosion-proof electrical/ventilating/lighting/equipment
P242: Use only non-sparking tools
P243: Take precautionary measures against static discharge
P280: Wear protective gloves/protective clothing/eye protection/face protection
P362+364: Take off contaminated clothing and wash it before reuse
P264: Wash skin thoroughly after handling
P271: Use only in a well-ventilated area
P260: Do not breathe dust/fume/gas/mist/vapours/spray
P202: Do not handle until all safety precautions have been read and understood
P270: Do not eat, drink or smoke when using this product
P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P332+313: If skin irritation occurs: Get medical advice/attention
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P310: Immediately call a POISON CENTER or doctor/physician
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P308+311: IF exposed or concerned: Call a POISON CENTER/doctor
P403+235: Store in a well ventilated place. Keep cool
P405: Store locked up
P370+378: In case of fire: Use foam, water fog, dry chemical and/or carbon dioxide to extinguish
P501: Dispose of contents/container to comply with local, provincial, state, and federal regulations

Safety Data Sheet - E15 OMNIPRIME NEUTRAL PRE-CATALYZED PRIMER

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	%
Xylene	1330-20-7	3.00-7.00
Ethyl Benzene	100-41-4	1.00-5.00
Isobutanol	78-83-1	1.00-5.00
Crystalline Silica - Quartz	14808-60-7	0.10-1.50
Hydrous Magnesium Silicate	14807-96-6	5.00-10.00
Ethyl Acetate	141-78-6	7.00-13.00
Methanol	67-56-1	7.00-13.00
Acetone	67-64-1	7.00-13.00
Butanol	71-36-3	1.00-5.00
Nitrocellulose	9004-70-0	3.00-7.00
Isopropanol	67-63-0	1.00-5.00
Di(2-ethylhexyl)Phthalate	117-81-7	1.00-5.00
Urea P/W Formaldehyde, isobutylated	68002-18-6	1.00-5.00
Melamine P/W Formaldehyde, butylated	68002-25-5	1.00-5.00
Ethanol	64-17-5	0.10-1.00

Refer to Section 8 for Occupational Exposure Guidelines.

SECTION 4 – FIRST-AID MEASURES

Inhalation:

This product is (extremely) flammable. Take proper precautions (e.g. remove any sources of ignition). If breathing is stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Quickly transport victim to an emergency care facility.

Ingestion:

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. Do not induce vomiting. Have victim drink 60-240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim rinse mouth with water again. Immediately obtain medical attention.

Eyes:

Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, do not delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.

Skin:

As quickly as possible, remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Immediately flush with lukewarm, gently flowing water for 15-20 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard. Immediately obtain medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

Note to Physician:

Treatment based on sound judgement of physician and individual reactions of patient.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media:

Carbon dioxide, alcohol foam, water fog, dry chemical.

Special Fire Fighting Procedures:

Use water spray to cool fire-exposed containers or structures.

Unusual Fire and Explosion Hazards:

Vapours and/or fumes from this product are heavier than air and may travel to a source of ignition and flash back causing explosion and fire. Never use welding or cutting torch on, or near drum (even empty) as product (even residue) can ignite explosively. All containers, including pails, drums, tank cars & trucks should be grounded and/or bonded when material is transferred. When using this product it is important that the gas at main leading to the premises must be shut off. All other ignition sources must be completely eliminated. In reference to the Ontario Fire Code Section 4.1.5.9(1), states that this product shall not be stored, handled or used in basements or pits.

Hazardous Combustion Products:

Carbon monoxide and/or carbon dioxide, various hydrocarbons Oxides of nitrogen, sulfur, barium, copper and phosphorous.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Dike and contain spills. Do not let product enter drains.

Methods and Materials for Containment and Clean Up:

Contain and/or dike spills. Absorb with inert material, place in a suitable container. Report and dispose of according to local regulations.

SECTION 7 – HANDLING AND STORAGE

Storage:

Keep container tightly closed in a dry and well-ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage and evaporation.

Handling:

Use in a well ventilated area. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof tools, equipment, and ventilation system. Keep away from sources of ignition. Take measures to prevent the build-up of electrostatic charge. Always ground and bond containers.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value: 5 mg/m³ ACGIH est. (Di(2-ethylhexyl)Phthalate)

Engineering Controls:

Use local, mechanical, explosion proof exhaust and/or ventilation system to avoid exposure and vapour accumulation.

Safety Data Sheet - E15 OMNIPRIME NEUTRAL PRE-CATALYZED PRIMER

Personal Protective Equipment:

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate, use an approved respirator for the concentration and type of hazardous materials in the workplace. Use respirators and components tested and approved under the appropriate government standards. Use respirators as backup to engineering controls if necessary.

Hand Protection:

Handle with gloves to minimize skin contact. Inspect gloves prior to use. Use proper glove removal technique (without touching the glove's outer surface) to avoid skin contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly.

Eye Protection:

Safety glasses and/or face shield. Use equipment for eye protection tested and approved under the appropriate government standards.

Protective Clothing:

Impervious clothing, flame retardant, antistatic protective clothing. The type of protective equipment should be selected according to the concentration and amount of hazardous materials at each specific workplace.

Additional Measures:

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and at the end of the workday.

SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

Physical State: Liquid
Appearance/Odour: Neutral to cream with solvent odour
Odour Threshold: Not available
Viscosity: 80-100 seconds @ 25°C #4 Ford Cup
Vapour Density (AIR=1): Heavier than air
Boiling Point: 56°C est. (Acetone)
Melting/Freezing Point: Not available
Vapour Pressure: Not available
Evaporation Rate: Not available
Specific Gravity: 1.1821 +/- 0.01 gms/cc @ 25°C
Solubility in Water: Insoluble
Total VOC's: 521 g/L
% Non-Volatile: 52% +/- 2 w/w
..... 34% +/- 2 w/v
Coeff. Water/Oil Dist.: Not available
Flashpoint: -16.99°C est. (Acetone)
Autoignition Temp: >343°C est.
Upper Flammable Limit: 36% est. (Methanol)
Lower Flammable Limit: 0.28% est. (Di(2-ethylhexyl)Phthalate)

SECTION 10 – STABILITY AND REACTIVITY

Stability:

Stable.

Hazardous Decomposition Products:

Carbon monoxide and/or carbon dioxide and various hydrocarbons. Sulfur, barium, nitrogen oxides, phosphorous oxides.

Materials to Avoid:

Strong acids, bases and oxidizing agents. Ammonia, reducing materials, some metals and metal alloys, amines, peroxides, phosphorous oxychloride, alkalis, halogens. Attacks some types of rubber and plastic. May be corrosive to lead and aluminum.

Hazardous Reactions:

No data.

Conditions to Avoid:

Heat, flames and sparks.

SECTION 11 – TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT	LD50	LC50	HRS
Xylene	3523 mg/kg	5000 ppm	4
Ethyl Benzene	3500 mg/kg	4000 ppm	4
Isobutanol	2500 mg/kg	8000 ppm	4
Crystalline Silica - Quartz	500 mg/kg	12.6 mg/L	4
Hydrous Magnesium Silicate	not available	not available	-
Ethyl Acetate	5620 mg/kg	19600 ppm	4
Methanol	5628 mg/kg	64000 ppm	4
Acetone	5800 mg/kg	30000 ppm	4
Butanol	790 mg/kg	8000 ppm	4
Nitrocellulose	>5000 mg/kg	not available	-
Isopropanol	>5840 mg/kg	30 mg/L	4
Di(2-ethylhexyl)Phthalate	30000 mg/kg	>10.62 mg/L	4
Urea P/W Formaldehyde, isobutylated	>2000 mg/kg	>5 mg/L	4
Melamine P/W Formaldehyde, butylated	not available	not available	-
Ethanol	7060 mg/kg	31623 ppm	4
.	.	16% of total product has unknown toxicity	.

Skin corrosion/irritation:

Rabbit - skin irritation - 24 hour

Serious eye damage/irritation:

A component of this product tested: Rabbit - blindness - OECD test guideline 405

Respiratory or skin sensitization:

Not classified as a sensitization hazard.

Germ cell mutagenicity:

Not expected to be mutagenic in humans.

Safety Data Sheet - E15 OMNIPRIME NEUTRAL PRE-CATALYZED PRIMER

Carcinogenicity:

IARC has classified Crystalline Silica Quartz as carcinogenic to humans, Group 1.

IARC has classified Ethyl Benzene as a possible human carcinogen, Group 2B.

IARC has classified Di(2-ethylhexyl)Phthalate as a possible human carcinogen, Group 2B. The data available from epidemiological studies is inadequate to evaluate the relationship between human cancer and exposure specifically to DEHP (IARC 1982).

Reproductive toxicity:

Excessive exposure during pregnancy may be hazardous to the developing fetus. May cause fetotoxic effects at doses which are not maternally toxic, based on animal studies.

Teratogenicity:

May cause teratogenic/embryotoxic effects at high doses.

Specific target organ toxicity (single exposure):

May cause central nervous system depression. Ingestion may cause damage to the optic nerve.

Specific target organ toxicity (repeated exposure):

May cause liver and/or kidney effects. May cause organ effects.

Aspiration hazard:

Not classified as an aspiration hazard.

Potential Health Effects:

Inhalation:

Prolonged exposure to high vapour concentration can lead to central nervous system depression. Signs of this include headache, nausea, dizziness, blurred vision and incoordination. Studies have linked excessive inhalation of crystalline silica, quartz in dust form with chronic respiratory disease. Coatings risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

Ingestion:

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Can cause central nervous system effects including; dizziness, weakness, fatigue, nausea, headache, blurred vision and possible unconsciousness. Contains Methanol. Cannot be made non-poisonous. Swallowing even small amounts of Methanol can cause blindness.

Skin:

Prolonged and repeated contact can cause defatting and drying of the skin resulting in irritation and dermatitis. Can be absorbed in toxic amounts, especially from prolonged and repeated exposure.

Eyes:

May cause severe irritation, redness, tearing, burning sensation, swelling and/or blurred vision.

Signs and Symptoms of Exposure:

Can cause central nervous system effects, including dizziness, weakness, fatigue, nausea, headache, blurred vision and possible unconsciousness.

Synergistic effects:

Not available.

Additional information:

May cause central nervous system (CNS) depression. CNS depression is characterized by headache, dizziness, nausea, vomiting and incoordination.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental Fate and Distribution:

Prevent from entering drains, sewers, streams or other bodies of water. If runoff occurs, notify authorities as required.

Aquaticity:

LC50 (Pimephales Promelas) >0.67 mg/L, 96H est. (Di(2-ethylhexyl)Phthalate)
LC50 (Pimephales Promelas) 13.4 mg/L, flow-through, 96H est. (Xylene)

Persistence and degradability:

No data.

Bioaccumulative potential:

No data.

Mobility in soil:

No data.

Other adverse effects:

No data.

SECTION 13 –DISPOSAL CONSIDERATIONS

Waste disposal:

Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of in accordance with all applicable regulations.

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may retain product residue, follow any label warnings even after container is emptied.

SECTION 14 – TRANSPORTATION INFORMATION

TDG Classification (Ground Only):CLASS 3 UN1263 II

Proper Shipping Name (Ground Only):PAINT

A scientific determination was concluded based on formulation ingredients on August 29, 2019 to define the Transportation of Dangerous Goods Classifications.

SECTION 15 - REGULATIONS

This material is included on the DLS (Canadian Domestic Substance List) under the CEPA (Canadian Environmental Protection Act).

This material has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This material meets TSCA (Toxic Substances Control Act) inventory requirements.

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

SECTION 16 – OTHER INFORMATION

LEGEND TO ABBREVIATIONS:

CAS: CHEMICAL ABSTRACT SERVICES
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
LC: LETHAL CONCENTRATION
LD: LETHAL DOSE
TDG: TRANSPORTATION OF DANGEROUS GOODS
TLV: THRESHOLD LIMIT VALUE
VOC: VOLATILE ORGANIC COMPOUND

The information contained in this form is based on data from sources considered to be reliable but Katilac Coatings Inc. does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Katilac Coatings Inc. expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.