



**SECTION 1 – PRODUCT IDENTIFICATION AND COMPANY IDENTIFICATION**

**Manufacturer/Supplier:** ..... KATILAC COATINGS INC.  
391 HANLAN ROAD, UNIT #1, WOODBRIDGE, ONTARIO L4L 3T1  
**Phone:**..... 905-856-6464  
840 APPLEBY LINE, BURLINGTON, ONTARIO L7L 2Y7  
**Phone:**..... 905-637-2931  
www.katilaccoatings.com

**Emergency Phone:**..... CANUTEC (24H)...1-888-CANUTEC (226-8832 North American use)  
.....1-613-996-6666 (International use)

**Poison Control:**..... 1-800-268-9017

**Revision Date:**..... March 2, 2020  
**Print Date:**..... February 3, 2020  
**Version Number:**..... 2

**Product:** ..... FK8 PURESEAL FORMALDEHYDE FREE VINYL SEALER  
**Product Use:** ..... INDUSTRIAL SEALER FORMALDEHYDE FREE  
FOR INDUSTRIAL USE ONLY

**SECTION 2 – HAZARDS IDENTIFICATION**

**Emergency Overview**

**Target Organs:**

Central nervous system, eyes, skin, respiratory system, reproductive system, optic nerve.


**GHS Classification:**

- Flammable Liquids (Cat. 2)
- Skin Irritation (Cat. 3)
- Serious Eye Damage (Cat. 1)
- Carcinogenicity (Cat. 2)
- Reproductive Toxicity (Cat. 1B)
- Specific Target Organ Toxicity- Single Exposure (Cat. 3) - Central Nervous System, Respiratory Irritation
- Specific Target Organ Toxicity- Single Exposure (Cat. 2) - Ingestion may damage optic nerve

# Safety Data Sheet - FK8 PURESEAL FORMALDEHYDE FREE VINYL SEALER

## GHS Label Elements, including precautionary statements:

### Pictogram:



**Signal Word:**..... **Danger**

### Hazard Statement(s):

- H225: Highly flammable liquid and vapour
- H316: Causes mild skin irritation
- H318: Causes serious eye damage
- H351: Suspected of causing cancer
- H360: May damage fertility or the unborn child
- H336: May cause drowsiness or dizziness
- H335: May cause respiratory irritation
- H371: May cause damage to organs

### Precautionary Statement(s):

- P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
- P233: Keep container tightly closed
- P240: Ground/bond container and receiving equipment
- P241: Use explosion-proof electrical/ventilating/lighting/equipment
- P242: Use only non-sparking tools
- P243: Take precautionary measures against static discharge
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P260: Do not breathe dust/fume/gas/mist/vapours/spray
- P271: Use only in a well-ventilated area
- P264: Wash skin thoroughly after handling
- P270: Do not eat, drink or smoke when using this product
- P202: Do not handle until all safety precautions have been read and understood
- P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P302+352: IF ON SKIN: Wash with soap and water
- P332+313: If skin irritation occurs: Get medical advice/attention
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
- P310: Immediately call a POISON CENTER or doctor/physician
- P308+313: IF exposed or concerned: Get medical advice/attention
- P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P312: Call a POISON CENTER or doctor/physician if you feel unwell
- P403+235: Store in a well ventilated place. Keep cool
- P405: Store locked up
- P370+378: In case of fire: Use foam, water fog, dry chemical and/or carbon dioxide to extinguish
- P501: Dispose of contents/container to comply with local, provincial, state, and federal regulations

**SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT	CAS NUMBER	%
Butanol	71-36-3	5.00-10.00
Ethyl Alcohol	64-17-5	7.00-13.00
Methanol	67-56-1	1.00-5.00
Ethyl Acetate	141-78-6	15.00-40.00
n-Butyl Acetate	123-86-4	10.00-30.00
Nitrocellulose	9004-70-0	3.00-7.00
Isopropanol	67-63-0	1.00-5.00
Di(2-ethylhexyl)Phthalate	117-81-7	1.00-5.00

Refer to Section 8 for Occupational Exposure Guidelines.

**SECTION 4 – FIRST-AID MEASURES**

**Inhalation:**

This product is (extremely) flammable. Take proper precautions (e.g. remove any sources of ignition). Take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If breathing is stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Quickly transport victim to an emergency care facility.

**Ingestion:**

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Have victim drink 60-240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim rinse mouth with water again. Obtain medical advice.

**Eyes:**

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, do not delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.

**Skin:**

Remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with lukewarm gently flowing water and non-abrasive soap for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

**Note to Physician:**

Treatment should be based on sound judgement of physician and individual reactions of patient.

**SECTION 5 – FIRE-FIGHTING MEASURES**

**Extinguishing Media:**

Carbon dioxide, alcohol foam, water fog, dry chemical.

**Special Fire Fighting Procedures:**

Use water spray to cool fire-exposed containers or structures.

## Safety Data Sheet - FK8 PURESEAL FORMALDEHYDE FREE VINYL SEALER

### **Unusual Fire and Explosion Hazards:**

Vapours and/or fumes from this product are heavier than air and may travel to a source of ignition and flash back causing explosion and fire. Never use welding or cutting torch on, or near drum (even empty) as product (even residue) can ignite explosively. All containers, including pails, drums, tank cars & trucks should be grounded and/or bonded when material is transferred. When using this product it is important that the gas at main leading to the premises must be shut off. All other ignition sources must be completely eliminated. In reference to the Ontario Fire Code Section 4.1.5.9(1), states that this product shall not be stored, handled or used in basements or pits.

### **Hazardous Combustion Products:**

Carbon monoxide and/or carbon dioxide. Nitrogen oxide.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

### **Personal Precautions:**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations.

### **Environmental Precautions:**

Prevent further leakage or spillage if safe to do so. Dike and contain spills. Do not let product enter drains.

### **Methods and Materials for Containment and Clean Up:**

Contain and/or dike spills. Absorb with inert material, place in a suitable container. Report and dispose of according to local regulations.

## SECTION 7 – HANDLING AND STORAGE

### **Storage:**

Keep container tightly closed in a dry and well-ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage and evaporation.

### **Handling:**

Use in a well ventilated area. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof tools, equipment, and ventilation system. Keep away from sources of ignition. Take measures to prevent the build-up of electrostatic charge. Always ground and bond containers.

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

**Threshold Limit Value:**..... 5 mg/m<sup>3</sup> ACGIH est. (Di(2-ethylhexyl)Phthalate)

### **Engineering Controls:**

Use local, mechanical, explosion proof exhaust and/or ventilation system to avoid exposure and vapour accumulation.

### **Personal Protective Equipment:**

#### **Respiratory Protection:**

Where risk assessment shows air-purifying respirators are appropriate, use an approved respirator for the concentration and type of hazardous materials in the workplace. Use respirators and components tested and approved under the appropriate government standards. Use respirators as backup to engineering controls if necessary.

## Safety Data Sheet - FK8 PURESEAL FORMALDEHYDE FREE VINYL SEALER

### Hand Protection:

Handle with gloves to minimize skin contact. Inspect gloves prior to use. Use proper glove removal technique (without touching the glove's outer surface) to avoid skin contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly.

### Eye Protection:

Safety glasses and/or face shield. Use equipment for eye protection tested and approved under the appropriate government standards.

### Protective Clothing:

Impervious clothing, flame retardant, antistatic protective clothing. The type of protective equipment should be selected according to the concentration and amount of hazardous materials at each specific workplace.

### Additional Measures:

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and at the end of the workday.

## SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

**Physical State:** ..... Liquid  
**Appearance/Odour:** ..... Water white, cloudy, with solvent odour  
**Odour Threshold:** ..... Not available  
**Viscosity:** ..... 25 seconds #4 Ford Cup @ 25°C  
**Vapour Density (AIR=1):** ..... Heavier than air  
**Boiling Point:** ..... 74-79°C est. (Ethyl Alcohol)  
**Melting/Freezing Point:** ..... Not available  
**Vapour Pressure:** ..... Not available  
**Evaporation Rate:** ..... Not available  
**Specific Gravity:** ..... 0.9500 +/- 0.01 gms/cc @ 25°C  
**Solubility in Water:** ..... Insoluble  
**Total VOC's:** ..... 691 g/L  
**% Non-Volatile:** ..... 26% +/- 2 w/w  
..... 19% +/- 2 w/v  
**Coeff. Water/Oil Dist.:** ..... Not available

**Flashpoint:** ..... -4°C est. (Ethyl Acetate)  
**Autoignition Temp:** ..... 343°C est. (Butanol)  
**Upper Flammable Limit:** ..... 36.5% est. (Methanol)  
**Lower Flammable Limit:** ..... 0.3% est. (Di(2-ethylhexyl)Phthalate)

## SECTION 10 – STABILITY AND REACTIVITY

### Stability:

Stable.

### Hazardous Decomposition Products:

Carbon monoxide and/or carbon dioxide. Acetic acid, butyl alcohol, nitrogen oxide.

### Materials to Avoid:

Strong oxidizing agents, bases, acids, halogens, alkali metals, ammonia, reducing agents, potassium tert-butoxide, amines. Some rubbers and plastics.

# Safety Data Sheet - FK8 PURESEAL FORMALDEHYDE FREE VINYL SEALER

**Hazardous Reactions:**

No data.

**Conditions to Avoid:**

Heat, flames and sparks.

<b>SECTION 11 – TOXICOLOGICAL INFORMATION</b>
---

HAZARDOUS INGREDIENT	LD50	LC50	HRS
Butanol	790 mg/kg	8000 ppm	4
Ethyl Alcohol	7060 mg/kg	31623 ppm	4
Methanol	5628 mg/kg	64000 ppm	4
Ethyl Acetate	5620 mg/kg	19600 ppm	4
n-Butyl Acetate	10768 mg/kg	160-9312 ppm	4
Nitrocellulose	>5000 mg/kg	not available	-
Isopropanol	>5840 mg/kg	30 mg/L	4
Di(2-ethylhexyl)Phthalate	30000 mg/kg	>10.62 mg/L	4

**Skin corrosion/irritation:**

Rabbit - skin irritation - 24 hour

**Serious eye damage/irritation:**

A component of this product tested: Rabbit - blindness - OECD test guideline 405

**Respiratory or skin sensitization:**

Not classified as a sensitization hazard.

**Germ cell mutagenicity:**

Not expected to be mutagenic in humans.

**Carcinogenicity:**

IARC has classified Di(2-ethylhexyl)Phthalate as a possible human carcinogen, Group 2B. The data available from epidemiological studies is inadequate to evaluate the relationship between human cancer and exposure specifically to DEHP (IARC 1982).

**Reproductive toxicity:**

Excessive exposure during pregnancy may be hazardous to the developing fetus. May cause fetotoxic effects at doses which are not maternally toxic, based on animal studies.

**Teratogenicity:**

Not available.

**Specific target organ toxicity (single exposure):**

May cause central nervous system depression. May cause respiratory system irritation. Ingestion may cause damage to the optic nerve.

**Specific target organ toxicity (repeated exposure):**

Not classified as a repeat exposure hazard.

**Aspiration hazard:**

Not classified as an aspiration hazard.

**Potential Health Effects:****Inhalation:**

May cause nasal and respiratory irritation. Excessive inhalation of vapours can cause nasal and respiratory irritation and central nervous system effects, including dizziness, weakness, fatigue, nausea, headache, blurred vision and possible unconsciousness.

## Safety Data Sheet - FK8 PURESEAL FORMALDEHYDE FREE VINYL SEALER

### **Ingestion:**

Causes irritation, burning sensation of the mouth, throat, and respiratory tract and abdominal pain. May cause liver damage, kidney damage, central nervous system (cns) depression, headache, dizziness, diarrhea, nausea, and vomiting. Contains methanol. Cannot be made non-poisonous. Swallowing even small amounts can cause blindness.

### **Skin:**

Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

### **Eyes:**

May cause severe irritation, redness, tearing, blurred vision.

### **Signs and Symptoms of Exposure:**

Overexposure may cause central nervous system effects. May irritate skin. Can cause reproductive effects.

### **Synergistic effects:**

Not available.

### **Additional information:**

May cause central nervous system (CNS) depression. CNS depression is characterized by headache, dizziness, nausea, vomiting and incoordination. Contains Methanol. Cannot be made non-poisonous. Swallowing even small amounts of Methanol can cause blindness.

## SECTION 12 – ECOLOGICAL INFORMATION

### **Environmental Fate and Distribution:**

Prevent from entering drains, sewers, streams or other bodies of water. If runoff occurs, notify authorities as required.

### **Aquaticity:**

LC50 (Pimephales Promelas) >0.67 mg/L, 96H est. (Di(2-ethylhexyl)Phthalate)

LC50 (Pimephales Promelas) 18 mg/L, 96H, OECD Test Guideline 203, est. (n-Butyl Acetate)

### **Persistence and degradability:**

No data.

### **Bioaccumulative potential:**

No data.

### **Mobility in soil:**

No data.

### **Other adverse effects:**

May be harmful to aquatic life.

## SECTION 13 –DISPOSAL CONSIDERATIONS

### **Waste disposal:**

Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of in accordance with all applicable regulations.

### **Contaminated Packaging:**

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may retain product residue, follow any label warnings even after container is emptied.

**SECTION 14 – TRANSPORTATION INFORMATION**

**TDG Classification (Ground Only):** .....CLASS 3 UN1263 II  
**Proper Shipping Name (Ground Only):** .....PAINT

*A scientific determination was concluded based on formulation ingredients on March 2, 2020 to define the Transportation of Dangerous Goods Classifications.*

**SECTION 15 - REGULATIONS**

This material is included on the DLS (Canadian Domestic Substance List) under the CEPA (Canadian Environmental Protection Act).

This material has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This material meets TSCA (Toxic Substances Control Act) inventory requirements.

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

**SECTION 16 – OTHER INFORMATION**

**LEGEND TO ABBREVIATIONS:**

**CAS:** ..... CHEMICAL ABSTRACT SERVICES  
**IARC:** ..... INTERNATIONAL AGENCY FOR RESEARCH ON CANCER  
**LC:** ..... LETHAL CONCENTRATION  
**LD:** ..... LETHAL DOSE  
**TDG:** ..... TRANSPORTATION OF DANGEROUS GOODS  
**TLV:** ..... THRESHOLD LIMIT VALUE  
**VOC:** ..... VOLATILE ORGANIC COMPOUND

The information contained in this form is based on data from sources considered to be reliable but Katilac Coatings Inc. does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Katilac Coatings Inc. expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.