



KATILAC COATINGS INC.

Where quality is ingrained

SECTION 1 – IDENTIFICATION

Product: T4424 LACQUER THINNER FAST

Product Use: INDUSTRIAL THINNER

.....FOR INDUSTRIAL USE ONLY

Manufacturer/Supplier: KATILAC COATINGS INC.

391 HANLAN ROAD, UNIT #1, WOODBRIDGE, ONTARIO L4L 3T1

Phone:..... 905-856-6464 (Monday-Friday 8:00-4:00)

840 APPLEBY LINE, BURLINGTON, ONTARIO L7L 2Y7

Phone:..... 905-637-2931 (Monday-Friday 8:00-4:00)

www.katilaccoatings.com

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification:

Flammable Liquids (Cat. 2)

Skin Irritation (Cat. 2)

Eye Irritation (Cat. 2A)

Reproductive Toxicity (Cat. 2)

Specific Target Organ Toxicity- Single Exposure (Cat. 3) - Central Nervous System

Specific Target Organ Toxicity- Single Exposure (Cat. 2) - Ingestion may damage optic nerve, central nervous system

Specific Target Organ Toxicity - Repeated Exposure (Cat. 2) - Nervous System

Aspiration Hazard (Cat. 1)

GHS Label Elements:

Pictogram:



Signal Word:..... **Danger**

Target Organs:

Central nervous system, eyes, skin, reproductive system, optic nerve.

Safety Data Sheet - T4424 LACQUER THINNER FAST

Hazard Statement(s):

H225: Highly flammable liquid and vapour
H315: Causes skin irritation
H319: Causes serious eye irritation
H361: Suspected of damaging fertility or the unborn child
H336: May cause drowsiness or dizziness
H371: May cause damage to organs - ingestion may damage optic nerve, central nervous system
H373: May cause damage to organs through prolonged or repeated exposure
H304: May be fatal if swallowed and enters airways

Precautionary Statement(s):

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting and equipment.
P242: Use non-sparking tools.
P243: Take action to prevent static discharges.
P280: Wear protective gloves, protective clothing, eye protection.
P264: Wash skin thoroughly after handling.
P260: Do not breathe dust, fumes, mist, vapours or spray.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P302+P352: IF ON SKIN: Wash with plenty of water.
P332+P313: If skin irritation occurs: Get medical attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical attention.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor.
P312: Call a POISON CENTER or doctor if you feel unwell.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER.
P331: Do NOT induce vomiting.
P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.
P370+P378: In case of fire: Use foam, water fog, dry chemical and/or carbon dioxide to extinguish.
P501: Dispose of contents and container to comply with local, provincial, state, and federal regulations.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	% wt/wt
Toluene	108-88-3	45.00-70.00
Methanol	67-56-1	5.00-10.00
Ethyl Acetate	141-78-6	15.00-40.00

SECTION 4 – FIRST-AID MEASURES

Inhalation:

This product is (extremely) flammable. Take proper precautions (e.g. remove any sources of ignition). Take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment, use the buddy system). If breathing is stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Quickly transport victim to an emergency care facility.

Safety Data Sheet - T4424 LACQUER THINNER FAST

Ingestion:

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. Do not induce vomiting. Have victim drink 60-240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Immediately obtain medical attention.

Eyes:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, do not delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.

Skin:

As quickly as possible, remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Immediately flush with lukewarm, gently flowing water for 15-20 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

Most Important Symptoms and Effects:

May cause central nervous system (CNS) depression. CNS depression is characterized by headache, dizziness, nausea, vomiting and incoordination. Contains Methanol. Cannot be made non-poisonous. Swallowing even small amounts of Methanol can cause blindness.

Indication of Immediate Medical Attention and Special Treatment:

Treatment should be based on sound judgement of physician and individual reactions of patient. Consult a poison control centre for guidance.

SECTION 5 – FIRE-FIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media:

Foam, water fog, dry chemical, carbon dioxide. Do not use water jet.

Specific Hazards Arising from the Product:

Vapours and/or fumes from this product are heavier than air and may travel to a source of ignition and flash back causing explosion and fire. Never use welding or cutting torch on, or near drum (even empty) as product (even residue) can ignite explosively. All containers including cans, pails, drums, tank cars & trucks should be grounded and/or bonded when material is transferred.

Hazardous Combustion Products:

Carbon monoxide and/or carbon dioxide.

Special Fire Fighting Procedures:

Use water spray to cool fire-exposed containers or structures. Keep upwind of fire. Wear self-contained breathing apparatus and full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Use personal protective equipment recommended in Section 8. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations.

Methods and Materials for Containment and Clean Up:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Contain and dike spills. Absorb with inert material, place in a suitable container. Report and dispose of according to local regulations.

SECTION 7 – HANDLING AND STORAGE

Precautions for Safe Handling:

Use in a well-ventilated area. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof tools, equipment, and ventilation system. Keep away from sources of ignition. Take measures to prevent the build-up of electrostatic charge. Always ground and bond containers.

Conditions for Safe Storage:

Keep container tightly closed in a dry and well-ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage and evaporation. Avoid extreme temperatures.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value:

20 ppm ACGIH est. (Toluene)

200 ppm ACGIH est. (Methanol)

400 ppm ACGIH est. (Ethyl Acetate)

Engineering Controls:

Use local, mechanical, explosion proof exhaust and/or ventilation system to avoid exposure and vapour accumulation. Maintain exposure limits below the recommended thresholds.

Personal Protective Equipment:

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate, use an approved respirator for the concentration and type of hazardous materials in the workplace. Use respirators and components tested and approved under the appropriate government standards. Use respirators as backup to engineering controls if necessary.

Hand Protection:

Handle with gloves to minimize skin contact. Inspect gloves prior to use. Use proper glove removal technique (without touching the glove's outer surface) to avoid skin contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly.

Eye Protection:

Safety glasses with side shields and/or face shield. Use equipment for eye protection tested and approved under the appropriate government standards.

Protective Clothing:

Impervious clothing, flame retardant, antistatic protective clothing. The type of protective equipment should be selected according to the concentration and amount of hazardous materials at each specific workplace.

Additional Measures:

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and at the end of the workday. Do not eat, smoke or drink where material is handled, processed or stored.

SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

Physical State: Liquid

Colour/Odour: Clear, colourless with solvent odour

Melting/Freezing Point: -84°C est. (Ethyl Acetate)

Boiling Point: 64.7°C est. (Methanol)

Flammability: Not available

Upper Flammable Limit: 36.0% (v) est. (Methanol)

Lower Flammable Limit: 1.1% (v) est. (Toluene)

Safety Data Sheet - T4424 LACQUER THINNER FAST

Flashpoint: -4°C est. (Ethyl Acetate)
Autoignition Temp:..... 427°C est. (Ethyl Acetate)
Decomposition Temp:..... Not applicable based on normal workplace conditions
pH: Not available
Viscosity (kinematic):..... Not available
Solubility in Water: Not available
Partition Coefficient: n-octanol/water (logarithmic value) Not available
Vapour Pressure:..... Not available
Density:..... 0.87 @ 20°C
Vapour Density (AIR=1): Heavier than air
Particle Characteristics: Not applicable
Evaporation Rate: Not available
Total VOC's: 870 g/L

SECTION 10 – STABILITY AND REACTIVITY

Reactivity:

No data.

Chemical Stability:

Stable, except under fire conditions.

Possibility of Hazardous Reactions:

No hazardous reactions expected under normal handling conditions.

Conditions to Avoid:

Heat, flames and sparks, static / static discharge.

Incompatible Materials:

Strong oxidizing agents, strong alkalis, strong acids, strong bases, halogens and halogenated compounds, peroxides, nitrates, amines, isocyanates. Some metals and their alloys including lead, aluminum, copper, zinc, galvanized steel, cast iron. Some rubbers, plastics, coatings including natural, butyl, neoprene, nitrile, PVC. Violent explosion can occur between ethyl acetate and lithium aluminum.

Hazardous Decomposition Products:

Occurrence of decomposition products depend on temperature, air supply and presence of other materials. Carbon monoxide and/or carbon dioxide.

SECTION 11 – TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT	LD50	LC50	HRS
Toluene	>5580 mg/kg	28.1 mg/L	4
Methanol	5628 mg/kg	83.8 mg/L	4
Ethyl Acetate	5620 mg/kg	53.5 mg/L	4

Likely Routes of Exposure:

Skin: Can be absorbed in harmful amounts. Irritation, redness, burning sensation, drying, and cracking.

Eyes: Can cause irritation, redness, swelling, blurred vision.

Inhalation: Can cause central nervous system depression.

Ingestion: Harmful, may enter lungs. May cause blindness.

Skin corrosion/irritation:

Rabbit - skin irritation - 24 hour

Serious eye damage/irritation:

Classified as an eye irritant.

Respiratory or skin sensitization:

Not classified as a sensitization hazard.

Safety Data Sheet - T4424 LACQUER THINNER FAST

Germ cell mutagenicity:

Not expected to be mutagenic in humans.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity:

Excessive exposure during pregnancy may be hazardous to the developing fetus. Experiments have shown reproductive toxicity effects in male and female lab animals.

Teratogenicity:

May cause fetotoxic and/or embryotoxic effects at maternally toxic levels.

Specific target organ toxicity (single exposure):

May cause central nervous system depression. Ingestion may cause damage to the optic nerve.

Specific target organ toxicity (repeated exposure):

Classified as a repeat exposure hazard. May affect central nervous system with repeated exposure. Some studies also indicate possible impact to vision and the auditory system.

Aspiration hazard:

Classified as an aspiration hazard.

Potential Health Effects:

Inhalation:

Prolonged exposure to high vapour concentration can lead to central nervous system depression. Signs of this include headache, nausea, dizziness, blurred vision and incoordination.

Ingestion:

Irritation, abdominal pain, and burning sensation in mouth, throat, and respiratory tract; may cause CNS depression, visual disturbances, blindness, nausea, vomiting, systemic poisoning. Contains methanol. Cannot be made non-poisonous. Swallowing even small amounts of methanol may cause blindness.

Skin:

Prolonged and repeated contact can cause defatting and drying of the skin resulting in irritation and dermatitis.

Eyes:

May cause eye irritation. May cause tearing, burning sensation, redness, swelling, and/or blurred vision.

Signs and Symptoms of Exposure:

Can cause central nervous system effects, including dizziness, weakness, fatigue, nausea, headache, blurred vision and possible unconsciousness.

Additional Information:

May cause central nervous system (CNS) depression. CNS depression is characterized by headache, dizziness, nausea, vomiting and incoordination. Contains Methanol. Cannot be made non-poisonous. Swallowing even small amounts of Methanol can cause blindness.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:

LC50 (Oncorhynchus Mykiss) 5.5 mg/L, 96H, flow-through est. (Toluene)

LC50 (Lepomis Macrochirus) 15400 mg/L, 96H, flow-through est. (Methanol)

LC50 (Pimephales Promelas) 230 mg/L, 96H, flow-through est. (Ethyl Acetate)

Persistence and Degradability:

Readily biodegradable.

Bioaccumulative Potential:

log Pow: 2.73 @ 20°C / 3d bioconcentration factor (BCF): 90 est. (Toluene)

log Pow: -0.77 @ 25°C / 3d bioconcentration factor (BCF): 1.0 est. (Methanol)

log Pow: 0.73 @ 20°C / 3d bioconcentration factor (BCF): 30 est. (Ethyl Acetate)

Safety Data Sheet - T4424 LACQUER THINNER FAST

Mobility in Soil:

No data.

Other Adverse Effects:

May be toxic to aquatic life with potentially long lasting effects. Prevent from entering drains, sewers, streams or other bodies of water. If runoff occurs, notify authorities as required.

SECTION 13 –DISPOSAL CONSIDERATIONS

Waste Disposal:

Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of in accordance with all applicable regulations.

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may retain product residue, follow any label warnings even after container is emptied.

SECTION 14 – TRANSPORTATION INFORMATION

TDG Classification (Ground Only):CLASS 3 UN1263 II

Proper Shipping Name (Ground Only):PAINT RELATED MATERIAL

A scientific determination was concluded based on formulation ingredients on February 25, 2025 to define the Transportation of Dangerous Goods Classifications.

SECTION 15 - REGULATIONS

This material is included on the DLS (Canadian Domestic Substance List) under the CEPA (Canadian Environmental Protection Act).

This material has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This material meets TSCA (Toxic Substances Control Act) inventory requirements.

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

SECTION 16 – OTHER INFORMATION

Revision Date:..... February 25, 2025

Print Date:..... March 5, 2025

Version Number:..... 3

LEGEND TO ABBREVIATIONS:

CAS: CHEMICAL ABSTRACT SERVICES

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

LC: LETHAL CONCENTRATION

LD: LETHAL DOSE

TDG: TRANSPORTATION OF DANGEROUS GOODS

TLV: THRESHOLD LIMIT VALUE

VOC: VOLATILE ORGANIC COMPOUND

The information contained in this form is based on data from sources considered to be reliable but Katilac Coatings Inc. does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Katilac Coatings Inc. expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.